

Etabloc 065-050-125 GG

ETB 065-050-125-GGSBV66 WSECX2HHB

Operating point 1

Dimensioning operating point

Operating conditions (purchaser requirements)

Target flow rate		Vapour pressure determined	0.07945 bar.a
Target head		Specified inlet pressure	1 bar.r
Fluid	Antifreeze on propylene glycol base, inhibited, closed system, e.g. Antifrogen L or similar products	NPSH available	19.13 m
		Specified ambient temperature	40 °C
		Installation altitude above sea level	1,000 m
Fluid variant	Concentration 40%		
Specified fluid temperature	45 °C		
Density Fluid handled	1,024 kg/m ³		
Kinematic viscosity Fluid handled	2.115 mm ² /s		

Operating conditions (performance)

Flow rate	43.9 m ³ /h	Maximum power input at duty point	3.625 kW
Minimum permissible flow rate	12.37 m ³ /h	Maximum power input / curve	5.017 kW
Maximum permissible flow rate	50.19 m ³ /h	Pump speed	2,958 1/min
Pump set		Shut-off discharge pressure	3.303 bar.r
Maximum permissible flow rate	101.51 m ³ /h		
Head	21 m		
Shut-off head	22.93 m		
Efficiency Pump	70.91 %		
NPSH required	2.74 m		

Design data pump

Scope of supply Pump supplied by KSB	Pump + motor	Mains voltage	400 V
Pump standard	EN 733	Mains frequency	50 Hz
Shaft axis position	Horizontal	Minimum efficiency index MEI	0.7
Pump design	Close-coupled	Minimum permissible fluid temperature	-30 °C
Pump system design	Single-pump system	Maximum permissible fluid temperature	110 °C
Pump direction of rotation, viewed from casing side	Counterclockwise	Quantity Stages, single-entry	1
Hydraulic impeller diameter	130.3 mm	Casing wear ring design suction-side	Flat
Impeller type	Radial, closed, multi-channel	Casing wear ring design discharge-side	Flat
Free passage	11.6 mm	Installation chamber Casing cover	Conical (A-type cover)
Support foot	No	Bearing bracket size / shaft unit	25
		Pump directive	CE

Etabloc 065-050-125 GG

ETB 065-050-125-GGSBV66 WSECX2HHB

Nozzle connections pump

Nominal diameter Suction nozzle	DN 65	Nominal diameter Discharge nozzle	DN 50
Nominal pressure Suction nozzle	PN 16	Nominal pressure Discharge nozzle	PN 16
Suction nozzle position	Axial	Discharge nozzle position	0 deg
Suction nozzle design acc.to	EN1092-2	Discharge nozzle design acc.to	EN1092-2
Suction flange bolt hole pattern as per standard	EN1092-2	Discharge flange bolt hole pattern as per standard	EN1092-2
Flange facing type Inlet	Raised face (B,RF)		
Flange facing type Outlet	Raised face (B,RF)		

Auxiliary connections pump

6B Fluid Drain	G 1/4 Drilled and plugged	1M Pressure gauge Discharge nozzle	Without Without
6D Fluid Filling and venting	G 1/4 Drilled and plugged	1M Pressure gauge Suction nozzle	Without Without
5B Venting and drain	G 1/4 Drilled and plugged		

Shaft sealing

Shaft seal type	Single mechanical seal; seal chamber can be vented (A-type casing cover) - AV	Shaft seal code	Code 66
		Shaft seal manufacturer inboard	BURGMANN
Operating mode of mechanical seal (function)	API plan 03	Mechanical seal type inboard	EMG13G6
Determined pressure Seal chamber	1.13 bar.r	Material Shaft seal inboard	Q7Q7EGG-Y10 DW001

Materials

Material Volute casing (102)	EN-GJL-250/A48 CL 35B	Material Bolts/Screws Volute casing (902.01)	8.8
Material Casing cover (161)	EN-GJL-250/A48 CL 35B	Material Nut Impeller fastening (920.95)	(ST)
Material Shaft	C45+N		
Material Impeller (230)	EN-GJL-250/A48 CL 35B		
Material Casing wear ring suction-side (502.01)	JL/LAMELLAR GRAPHITE CAST IRON		
Material Casing wear ring discharge-side (502.02)	JL/LAMELLAR GRAPHITE CAST IRON		
Material Shaft protecting sleeve (523)	(CRNIMO ST INT)		
Material Static seal Discharge cover	DPAF DW001		
Material Drive lantern	EN-GJL-250/A48 CL 35B		

Etabloc 065-050-125 GG

ETB 065-050-125-GGSBV66 WSECX2HHB

Driver

Asynchronous motors	Yes	Rated speed Motor	2,930 1/min
Drive concept	Electric actuator	Number of motor poles	2
Drive standard, mechanical	IEC	Rated power Motor	5.5 kW
Drive standard electric	IEC	Motor power reserve determined	51.7 %
Motor bearing, insulated	No	Rated voltage Motor	400 V
Motor manufacturer	KSB's choice	Motor winding	400 / 690 V
Customer supply Drive	No	Rated frequency Motor	50Hz
Motor construction type	IM V15 (IM2011) IEC 60034-7	Motor switching type	Delta
Motor size	132S	Rated current Motor	10.5 A
Efficiency class	IE3 (Premium)	Starting current ratio Ia/In	8.7
Material motor housing	AL	Cos phi at 4/4 load	0.82
Enclosure Motor	IP55 (TEFC)	Motor efficiency at 4/4 load	89.2 %
Thermal class	155 (F) according to IEC 60085	Limit value Maximum humidity Motor	30 g/m ³
Temperature sensor motor	3 PTC thermistors	Marking according to directive Drive	CE
Terminal box position of motor (looking at the motor shaft)	360 °	The values indicated are regarded as guaranteed values. They are applied to motors with a sinusoidal power supply within the permissible tolerances specified by IEC 60034-1. The values given on the name plate may be different.	
Motor housing feet position	180° (below)		
Operation on a frequency inverter permitted	Yes (acc to motor manufact)		
Sound pressure level Motor	71 dBa		
Type series Motor manufacturer	Acc. to motor manufacturer (IEC, IE3)		

Coating

Aggregate

Surface preparation	Free from dirt, grease, rust
Properties Primer coat	Hydro dip primer, water-dilutable
Thickness Primer coat	60 µm
Properties Top coat	Acrylate dispersion water-thinned
Thickness Top coat	40 µm
Colour Top coat	RAL5002 Ultramarine Blue

Etabloc 065-050-125 GG

ETB 065-050-125-GGSBV66 WSECX2HHB

Energy cost and Environmental Impact

Result

Estimated Product Carbon Footprint (cradle-to-gate) (CO₂eq) 491 kg

*

This PCF indication is based on the product mass assuming the typical shares of materials in use. The conversion rate between product mass and CO₂ emissions is based on several life cycle assessments acc. to ISO14040 / 14044 of sample products of the same type series. Objective and scope of these LCAs was defined as being limited to the manufacturing phase (cradle-to-gate). With regard to inputs, all materials, energy and auxiliary materials were accounted for, and with regard to outputs, emissions, scrap and waste were accounted for. The impact of outbound logistics is not covered. The assessments' input variables cover at least 95 % of the total product mass. The analysis focuses exclusively on the Global Warming Potential (EF3.0 Climate Change – total).

Packaging

Suitable for transport	Truck transport
Suitable for storage	Indoor storage
Packaging category	KSB's choice (A0)


Performance Curve (Pump)



Page: 1 / 1

Etabloc 065-050-125 GG

ETB 065-050-125-GGSBV66 WSECX2HHB




Curve Data

Pump speed	2,958 1/min	Efficiency Pump	70.9 %
Density Fluid handled	1,024 kg/m^3	Minimum efficiency index MEI	0.7
Kinematic viscosity Fluid handled	2.12 mm^2/s	Maximum power input at duty point	3.62 kW
Flow rate	43.9 m^3/h	NPSH required	2.74 m
Maximum permissible flow rate	102 m^3/h	Hydraulic impeller diameter	130.3 mm
Head	21 m	Hydraulic calculation according to standard/class	EN ISO 9906 Class 3B

Etabloc 065-050-125 GG

ETB 065-050-125-GGSBV66 WSECX2HHB



Drawing is not to scale.

Dimensions are given in mm

Motor

Motor manufacturer	KSB's choice
Motor size	132S
Rated power Motor	5.5 kW
Number of motor poles	2
Rated speed Motor	2,930 1/min
Terminal box position of motor (looking at the motor shaft)	360 °
Motor housing feet position	180° (below)

Connections

Nominal diameter Suction nozzle	DN 65
Suction flange bolt hole pattern as per standard	EN1092-2
Nominal diameter Discharge nozzle	DN 50
Discharge flange bolt hole pattern as per standard	EN1092-2
Nominal pressure Suction nozzle	PN 16
Nominal pressure Discharge nozzle	PN 16



Etabloc 065-050-125 GG

ETB 065-050-125-GGSBV66 WSECX2HHB

Net weight

Total weight Pump	32.55 kg
Total weight Drive	57 kg
Total weight Pump set	89.55 kg
Total weight Assembly/transport aids	2.4 kg

Connect pipelines stress-free

Dimensional tolerances for shaft axis height: DIN 747
Dimensions without tolerances, middle tolerances to: ISO 2768-m
Connection dimensions for pumps: EN735
Dimensions without tolerances - welded parts: ISO 13920-B
Dimensions without tolerances - gray cast iron parts: ISO 8062-CT9

Plan for additional connections see extra drawing